



- › Various power output options (60-180kW)
- › Double socket control system with isolated circuits
- › OCPP 1.6
- › Ethernet, Wi-Fi or 4G communication support
- › Real-time data display via Internet portal
- › 2x CCS2 Charging Sockets
- › Charging two vehicles at the same time
- › 7" LCD touch screen
- › Built-in RFID reader
- › Eco saving mode
- › All-weather powder-coated stainless steel enclosure
- › 5 meters long cable with CCS2 nozzle

MODEL	60kW	90kW	120kW	180kW
Charging Voltage	DC			
Charging Standard	CCS2			
Number of Charging Points	2			
Input Voltage Range [VAC]	400 / 380 ± 10%			
Input Frequency [Hz]	50 / 60			
Output Power [kW]	60	90	120	180
DC Output Voltage range [VDC]	200-750			
Cable Length	Default 5m, optional 6m / 7m			
Current [A]	150	150	200	200
Connector Type	3P + N + PE			
Data Transmission via	GSM, 4G, LTE			
USER INTERFACE				
Data Access	Internet access via 4G/3G/Ethernet (RJ45)			
User Authentication	RFID, QR code			
User Interface	7" LCD high contrast touch screen			
Communication Protocol	OCPP 1.6			
PHYSICAL CHARACTERISTICS				
Protection Class	IP54			
Max. Operation Altitude [m]	2000			
Operating Temperature [°C]	-35 ~ 55			
Storage Temperature [°C]	-40 ~ 70			
Dimensions (D x W x H)[mm]	850 x 740 x 1830			

* TommaTech® GmbH reserves the right to change the specification of products without prior notice.