



- › 22kW and 2x22kW power output options
- › Electrical circuits compatible with all electric vehicles that in compliance with the standards of the EU.
- › OCPP 1.6
- › Ethernet, Wi-Fi or 4G communication support
- › Real-time data display via Internet portal
- › Start/finish with RFID card, credit card or cell phone app
- › Type2 charger socket
- › Remote software update support
- › Providing enough power to travel 100km after 1 hour of charging (Average value may vary depending on the vehicle)
- › 7" touch TFT display

MODEL	22kW	44kW
Charging Voltage	AC	
Charging Standard	Type 2	
Number of Charging Points	1	2
Input Voltage Range [VAC]	400 / 380 ± 10%	
Input Frequency [Hz]	50 / 60	
Output Power [kW]	22	2 x 22
Cable Length	Optional	
Current [A]	32	64
Residual Current Protection [mA]	30	
Connector Type	3P + N + PE	
Data Transmission via	GSM, 4G, LTE	
USER INTERFACE		
Data Access	Internet access via 4G/3G/Ethernet (RJ45)	
User Authentication	RFID, QR Code	
User Interface	128x64 OLED Display	7" TFT Display
Communication Protocol	OCPP 1.6	
PHYSICAL CHARACTERISTICS		
Protection Class	IP54	
Max. Operation Altitude [m]	2000	
Operating Temperature [°C]	-35 ~ 55	
Storage Temperature [°C]	-40 ~ 70	
Dimensions (D x W x H) [mm]	165 x 295 x 540	195 x 295 x 540

* TommaTech® GmbH reserves the right to change the specification of products without prior notice.